



Professional equipment for the refrigeration of beverages. Available in versions with 1 to 3 tanks, with a capacity of 5 or 8 liters.

Certifications



Available Voltages

230V 50Hz / 240V 50Hz / 115V 60Hz / 208-220V 60Hz / 100V 50-60Hz

Technical Specifications	Compact 5/1	Compact 5/2	Compact 5/3	Compact 8/1	Compact 8/2	Compact 8/3
Capacity (L)	5	10	15	8	16	24
Height (cm)	55	55	55	62	62	62
Width (cm)	18	25	37	18	25	37
Depth (cm)	39	39	39	41	41	41
Net Weight (Kg)	13	17	22	14	17	22
Gross Weight (Kg)	14	18	24	15	19	24
Power * (W)	250	350	550	250	350	550
Gas	R290	R290	R290	R290	R290	R290

Additional Technical Features	Safety and control devices
Shatterproof container made of Polycarbonate	Noise level below 70 dB(A)
Stainless steel bodywork	Models with R290 gas: equipped with ATEX electrical components
Air-cooled condenser	Hermetic compressor equipped with a protector
Rubberized tap	Mechanical temperature control (internal)
Magnetic drag mixing	Ease of disassembly and cleaning
Components suitable for food contact	

Optional Accessories

Gravity tap