



Professional equipment for beverage refrigeration. Available in models with 1 to 3 tanks with capacities of 12 or 20 liters. Fountain pump model (P version).

#### Certifications



#### Available Voltages

230V 50Hz / 240V 50Hz / 115V 60Hz / 208-220V 60Hz / 100V 50-60Hz

Technical Specifications	Deluxe 12/1	Deluxe 12/2	Deluxe 12/3	Deluxe 20/1	Deluxe 20/2	Deluxe 20/3
Capacity (L)	12	24	36	20	40	60
Height (cm)	57	57	57	67	67	67
Width (cm)	18	36	54	18	36	54
Depth (cm)	48	48	48	48	48	48
Net weight, approx. (Kg)	17	23	37	18	26	42
Gross weight, approx. (Kg)	19	26	40	20	29	45
Power * (W)	200	500	750	200	500	750
Gas	R290	R290	R290	R290	R290	R290
Gas (220V 60Hz, 100 / 115V 50 / 60Hz)	R134a	R134a	R448a	R134a	R134a	R448a

Additional Technical Features	Safety and control devices
Shatterproof polycarbonate container	Noise level below 70 dB (A)
Stainless steel body	R290 gas models: equipped with ATEX electrical components
Air-cooled condenser	Hermetic compressor with protector
Rubber tap	Internal mechanical product temperature control
Magnetic drive mixing	Easy to disassemble and clean

Optional Accessories	
Gravity tap	Gravity tap with stirrer
Product lighting	Illuminated cover