







Professional equipment for preparing gelato creams, cold creams, sorbets, and granitas. Includes a cup presence sensor and display.

Certifications







Available Voltages

230V 50Hz / 240V 50Hz / 115V 60Hz / 208-220V 60Hz / 100V 50-60Hz

Technical Specifications	MiniGEL Plus 1	MiniGEL Plus 2	MiniGEL Plus 3
Capacity (L)	6	12	18
Height (cm)	62	62	62
Width (cm)	20	40	60
Depth (cm)	48	48	48
Net weight, approx. (Kg)	27	47	62
Gross weight, approx. (Kg)	29	51	65
Power * (W)	350	650	800
Gas	R290	R290	R290
Gas (220V 60Hz, 100 / 115V 50 / 60Hz)	R134a	R448	R448a

Additional Technical Features	Safety and control devices
Shatterproof polycarbonate container	Noise level below 70 dB (A)
Re-COVER: for energy savings and reduced condensation	R290 gas models: equipped with ATEX electrical components
POM plastic stirrer	Hermetic compressor with protector
Painted steel and ABS body	Intuitive control panel
Air-cooled condenser	Electronic product density control
Lid unlocking button	Electronic product temperature control
Variable-speed brushless motor	Pre-equipped for tap lock
Mechanical transmission	Easy to disassemble and clean
Tilted container for easy emptying	Day/night function
Cup presence sensor	Product temperature display
Illuminated cover	Timer for day/night function
Product lighting	Product temperature alarm

Optional Accessories		
Shatterproof PETG (Tritan) container - BPA free	Backlit graphics (LED technology)	
Container/lid unlocking with key	LED WALL (illuminated front display)	

We reserve the right to make changes without prior notice.

*Test conditions: 32°C - 230V 50Hz - 1st hour of operation