



Professional equipment for preparing cold creams, sorbets, and granitas. Also available in the ETC version (Electronic Temperature Control).

Certifications



Available Voltages

230V 50Hz / 240V 50Hz / 115V 60Hz / 208-220V 60Hz / 100V 50-60Hz

Technical Specifications	NG easy 10/1	NG easy 10/2	NG easy 10/3
Capacity (L)	10	20	30
Height (cm)	70	70	70
Width (cm)	20	40	60
Depth (cm)	50	50	50
Net weight, approx. (Kg)	27	45 / 43 *	62
Gross weight, approx. (Kg)	29	48 / 45 *	66
Power ** (W)	500	740	1100
Gas	R290	R290	R290
Gas (220V 60Hz, 100 / 115V 50 / 60Hz)	R134a	R448a	R448a

Additional Technical Features	Safety and control devices
Shatterproof, non-toxic polycarbonate container	Noise level below 70 dB (A)
Painted steel and ABS body	R290 gas models: equipped with ATEX electrical components
Tilted container for easy emptying	Hermetic compressor with protector
POM plastic stirrer	Mechanical product density control
Air-cooled condenser	Accessible mechanical temperature control (115V only)
Fixed-speed gear reducer	Pre-equipped for tap lock
Patented magnetic transmission	Accessible and cleanable condenser air filter
Lid unlocking button	Day/night function (production/maintenance mode)
Illuminated cover	Internal electronic temperature control (230V only)

Optional Accessories	
Re-COVER: for energy savings and reduced condensation	LED WALL: illuminated front display (LED technology)
Container/lid unlocking with key	Display (ETC version)
Timer for day/night function	Product temperature display (ETC version)
Automatic refill system (autofill)	

* With R290 Gas

We reserve the right to make changes without prior notice.

** Test conditions: 32°C - 230V 50Hz - 1st hour of operation